


TDC® NOTCHER [3/5/6 HEAD MODELS]


For fast and accurate gang notching of duct blanks.

TDC® NOTCHER comes standard with 5 notching heads.

The LOCKFORMER® TDC® NOTCHER will gang notch duct blanks as much as 6 times faster than notching by hand. The Hydraulic powered notch units have individual shutoff valves for positive control. Notch units are designed for fast and easy repositioning. A built in locking handle and a measuring scale makes notch location setup a simple task. Notch depth is also adjustable. The TDC® NOTCHER has a thickness capacity of 16 ga. / 1,6 mm in galvanized mild steel.



First pass uses combination heads TDC 1, 2, & 3



Second pass uses combination cleat heads drive A, B & C

The yellow circle represents the combination of heads being used

*Patterns shown are for 6 head models



SPEEDNOTCH MODEL 16 [3&5 HEAD MODELS]

Speednotch allows you to gang-notch sheet metal hydraulically up to 600% faster than by hand, without layout or scribing.

It's the perfect tool for preparing ductwork to receive bar, slip or "S" and other drive connections. So, its profitability is tremendous ... even on single piece set-up. Complete self-containment provides instantaneous setting from the front for up to 5 notches on materials up to 16 gauge with 3-1/4" to 10' stretch out and a foot switch permits one man, unskilled, to handle most notching jobs.



MODEL	CAPACITY	DEPTH OF POCKET/SIZE	OTHER	SPEED	MOTOR/VOLTAGE	DIMENSIONS/WEIGHT
TDC® NOTCHER [3/5/6 HEAD MODELS]	16 gauge mild steel 10 feet	2 7/16" for TDC® notch 1-1/2" for "V" notch	Available in 3, 5 and 6 head combinations	N/A	3 H.P. 230/460 volts, 60 cycle, 3phase, A.C. 1,600 RPM.	Length - 122" Width - 24" Height - 52" Passline - 45" Weight - 800 lbs.
SPEEDNOTCH MODEL 16 [3&5 HEAD MODELS]	16-28 gauge	N/A	N/A	N/A	3 H.P. 230/460 volts, 60 cycle, 3phase, A.C. 1,800 RPM	Length - 122" Width - 24" Height - 52" Passline - 45" Weight - 800 lbs.

www.hweiss.com